A7/V7 Option Switch Settings

Supported bill   Ruble 10, 50, 100, 500, 1000   5bills.

A7/V7 dip-switch settings and functions:

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
Reject Ruble 10	ON											
★ Accept Ruble 10	OFF											
Reject Ruble 50		ON										
★ Accept Ruble 50		OFF										
Reject Ruble 100			ON									
★ Accept Ruble 100			OFF									
Reject Ruble 500				ON								
★ Accept Ruble 500				OFF								
Reject Ruble 1000					ON							
★ Accept Ruble 1000					OFF							
High Acceptance						ON						
★ High Security						OFF						
Harness disable							ON					
★ Harness enable							OFF					
Inhibit Active High								ON				
★ Inhibit Active Low								OFF				
★ 1 pulse / Ruble 10									OFF	OFF		
2 pulse / Ruble 10									ON	OFF		
5 pulse / Ruble 10									OFF	ON		
20 pulse / Ruble 10									ON	ON		
★ Pulse Speed — 50ms on / 50ms off											OFF	OFF
Pulse Speed — 60ms on / 300ms off											ON	OFF
Pulse Speed — 30ms on / 50ms off											OFF	ON
Pulse Speed — 150ms on / 150ms off											ON	ON

◈ Factory configuration has all switches in the OFF position.

Note : (1) Reset the bill acceptor after setting the dip switch.

(2) SW7 and SW8 of the 8-switch DIP and the 4-switch DIP are for pulse protocol only.

A7 Interface Settings: 2

INTERFACE	SW1	SW2	SW3	SW4
★ Credit-Pulse Normal HIGH	ON			
Credit-Pulse Normal LOW	OFF			
Pulse Mode		ON		
★ RS232 Interface		OFF		
Reserved			ON	
★			OFF	
				ON
★				OFF

V7 Interface Settings: 3

INTERFACE	SW1	SW2	SW3	SW4
★ Scaling Factor (SF) = 100 Decimal Point Position (DPP) = 2	ON			
Scaling Factor (SF) = 1 Decimal Point Position (DPP) = 0	OFF			
Pulse Mode		ON		
★ MDB Interface		OFF		
Reserved			ON	
★			OFF	
				ON
★				OFF

★ Manufacture setting